



Gutenbergstraße 2d, 59174
Kamen, Germany
Tel. +49 (0) 151 64695831
Internet: <http://snalube.com>
e-mail: info@snalube.com

Product Information

Quelle QX – Advanced 10W40 SN

Description

This motor oil is based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a good detergency and dispersion
- a safe lubrication film at high temperatures
- a strong protection against wear, corrosion and foaming

Application

This all-round motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Specification

Performance level:

Performance level:
ACEA A3/B4
API SN/CF
MB 229.1
VW 501.01/505.00

Typical Characteristics

10W40 SN		
Property	Unit	Typical Values
Density at 15 °C	kg/l	0.87
Viscosity -15 °C	mPa.s	5830
Viscosity 40 °C	mm ² /s	94.4
Viscosity 100 °C	mm ² /s	14.1
Viscosity Index		153
Flash Point COC	°C	224
Pour Point	°C	-39
Total Base Number	mgKOH/g	10.4
Sulphate Ash	%	1.31