



SNA GmbH

Hochleistungs - Schmierstoffe



Gutenbergstraße 2d,
59174 Kamen,
Germany
Tel. +49 (0) 151
64695831
Internet:
<http://snalube.com> e-
mail:
info@snalube.com

Product Information

Quelle QX Cool X 50% Pink

Description

Quelle QX Cool X 50% is a "long life" OAT (Organic Additives Technology) automotive coolant based on Mono-ethylene-glycol and demineralized water with addition of additives to obtain the following properties:

- A perfect protection of all types of metals that are used in engines and cooling systems
- A neutral behavior towards seals, gaskets and hoses
- A very good resistance against formation of foam
- Nitrite, amine, phosphate and silicate free
- Colored pink

Application

This coolant may be used all the year round in the cooling systems of gasoline and diesel engines.

This coolant is ready for use and protects against freezing down to -38°C.

Specification

Performance level:

ASTM D3306/D4985/D6210
 Chrysler MS 9176
 Cummins 85T8-2
 DAF 74002
 Detroit Diesel
 Ford WSS-M97B44-D
 GM 6277M
 John Deere H 24 B1 & C1
 Mack 014GS 17004
 MAN 324 Typ SNF
 MB 326.3
 Leyland Trucks LTS 22 AF 10
 Renault 41-01-001/--S Type D
 Scania TB 1451
 Volkswagen VW TL 774-F (G12 Plus)
 Volvo VCS

Typical Characteristics

Coolant 50%		
Property	Unit	
Density at 15 °C, kg/l	Kg/l	1,070
Crystallizationpoint, °C	°C	-38

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website.