



Gutenbergstraße 2d,
59174 Kamen,
Germany
Tel. +49 (0) 151
64695831
Internet:
<http://snalube.com> e-
mail:
info@snalube.com

Description

Application

Specification

Typical Characteristics

Product Information

Quelle QX- Gear SYN X Range

Quelle QX - Gear SYN X Range of lubricants is a series of synthetic gear oils that are formulated to provide optimum wear protection in industrial gear sets, off-highway construction and mining applications where consistent performance is critical. Quelle QX - Gear SYN X Range of lubricants offer a unique approach to gear and system component lubrication through a focused formulation that provides the end user with maximum confidence. This range provide:

- Superior rust protection.
- Enhanced hydrolytic stability.
- Exceptional oxidation and thermal stability.
- Excellent anti-wear performance.

Quelle QX - Gear SYN X Range of lubricants is used where DIN 51517 Part 3/AIST 224 standards are required

Performance level:

ANSI/AGMA Standard 9005-E02
DIN 51517 Part 3
AIST 224

DIN 51517 Part 3							
Property	Unit	68	150	220	320	460	680
Viscosity 40 °C	mm ² /s	67.8	149.2	220.8	319.4	458.2	704
Viscosity 100 °C	mm ² /s	10.4	18.9	25.6	32.3	41.2	62.2
Viscosity Index		140	143	148	141	139	156
Timken OK Load Test	Kg/lb	34/75	34/75	34/75	34/75	34/75	34/75
FZG Gear Scuffing test	Failure Load stage	>12	>12	>12	>12	>12	>12
Pour Point	°C	-45	-36	-36	-36	-23	-27
Flash Point	°C	227	228	228	229	229	229
API Gravity		35.4	33.4	33	32.4	31	35
Specific gravity @16 °C		0.848	0.858	0.86	0.863	0.871	0.85

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.
You can download a recent material safety data sheet of this product on our website.