



Gutenbergstraße 2d,
59174 Kamen,
Germany
Tel. +49 (0) 151
64695831
Internet:
<http://snalube.com> e-
mail:
info@snalube.com

Description

Application

Specification

Typical Characteristics

Product Information

Quelle QX- Gear X Range - Mineral

Quelle QX - Gear X Range is high performance gear oil and general lubricating oil with good ageing stability and with additives to improve corrosion protection (combat ferrous and nonferrous metal corrosion caused by moisture).
Outstanding anti-wear characteristics, excellent protection against scuffing and micro Pitting.

APPLICATION

Universal gear oils for all industrial applications such as in bearings, knuckles, spur, bevel and worm drives

Performance level:

DIN 51 517: Part3 (2004)
ISO 6743-6: ISO 12925-1
US Steel 224
David Brown S1.53.10.

ISO 6743-6: ISO 12925-1								
Property	Unit	68	100	150	220	320	460	680
Density@ 15 °C	kg/m ³	886	890	894	896	900	901	918
Flash Point	°C	236	240	250	260	255	270	270
Viscosity 40 °C	mm ² /s	68	100	150	220	320	460	680
Viscosity 100 °C	mm ² /s	8.7	11.2	14.5	18.9	24	30.4	36.8
Viscosity Index		99	98	94	96	95	95	88

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.
You can download a recent material safety data sheet of this product on our website.