



SNA GmbH

Hochleistungs - Schmierstoffe



Gutenbergstraße 2d,
59174 Kamen,
Germany
Tel. +49 (0) 151
64695831
Internet:
<http://snalube.com> e-
mail:
info@snalube.com

Description

Application

Specification

Typical Characteristics

Product Information

Quelle QX – HiTech 5W30 SP

A fuel economy, synthetic, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

Performance level:

ACEA C3
API SP
VW 504.00/507.00
BMW Longlife-04
Porsche C30
MB 229.52
Opel OV0401547

5W30 SP		
Property	Unit	Typical Values
Density at 15 °C	kg/l	0.852
Viscosity -15 °C	mPa.s	5980
Viscosity 40 °C	mm ² /s	69.8
Viscosity 100 °C	mm ² /s	12.3
Viscosity Index		176
Flash Point COC	°C	224
Pour Point	°C	-42
Total Base Number	mgKOH/g	8.3
Sulphate Ash	%	0.75

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website.