

Gutenbergstrße 2d, 59174 Kamen, Germany Tel. +49 (0) 151 64695831 Internet: http://snalube.com email: info@snalube.com

Description

SNA GmbH Hochleistungs - Schmierstoffe



Product Information

Quelle QX- Moto 4T 10W40 - 20W50

Quelle QX – Moto 4T is a synthetic technology 4-Stroke lubricant. Excellent shear resistance protecting engine and gearbox. Smooth shifting. Meets JASO MA2 specifications for optimal wet clutch performance.

PROPERTIES

Good wear protection Thermal and oxidation stability Helps keep engines clean for smoother operation Helps extend engine life

Application

APPLICATION

For use in all types of four-stroke motorcycles and engines, especially Hero, Yamaha and Honda with <150 cc engines. Suitable for catalytic converters.

Specification

Performance level:

Meets and exceeds: API SL / SJ / SH / SG JASO MA / MA2

Typical Characteristics

4T - SL			
Property	Unit	10W40	20W50
Density @15°C	Kg/l	0.871	0.88
Viscosity 100 °C	mm²/s	13.82	18.5
Viscosity 40 °C	mm²/s	89.9	160
Viscosity Index		155	126
Pour Point	°C	-33	-30
Flash Point	°C	226	230
TBN	KOH/g	7.5	7.5

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

You can download a recent material safety data sheet of this product on our website.