



SNA GmbH
Hochleistungs - Schmierstoffe



Gutenbergstraße 2d,
59174 Kamen,
Germany
Tel. +49 (0) 151
64695831
Internet:
<http://snalube.com> e-
mail:
info@snalube.com

Description

Application

Specification

Typical Characteristics

Product Information

Quelle QX- M Racing 4T 10W50 SL

Quelle QX – M Racing 4T 10W-50 is a fully synthetic engine oil for modern, high performance 4-stroke sports bikes that increases engine acceleration and power Castrol under the most arduous riding conditions.

Advantages

- Ultimate performance in extreme riding friction
- Complies with requirements of catalyst equipped engines

APPLICATION

Quelle QX – M Racing 4T 10W-50 is designed for high performance 4-stroke sports bikes to deliver optimum power and protection in all riding conditions.

It is suitable for all makes of 4-stroke bikes, both carburetor or fuel injected where API SL (and below) and JASO MA or MA2 specifications are recommended.

Performance level:

API SL
JASO MA2

| 4T - SL | | |
|------------------|--------------------|-------|
| Property | Unit | 10w50 |
| Density @15 °C | Kg/l | 0.85 |
| Viscosity 100 °C | mm ² /s | 17 |
| Viscosity 40 °C | mm ² /s | 110 |
| Viscosity Index | | 168 |
| Pour Point | °C | -33 |
| Flash Point | °C | 205 |
| TBN | KOH/g | 9.8 |

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website.