



**SNA GmbH**  
Hochleistungs - Schmierstoffe



Gutenbergstraße 2d,  
59174 Kamen,  
Germany  
Tel. +49 (0) 151  
64695831  
Internet:  
<http://snalube.com> e-  
mail:  
[info@snalube.com](mailto:info@snalube.com)

## Description

## Product Information

### Quelle QX- Trans X

### Manual Transmission Range

Quelle QX - Trans X Range is a high-performance, high-pressure gear oil manufactured from high quality mineral base oils and multifunctional "extreme pressure" additives.

Highest pressure-absorption capability  
Wear reduction  
Noise reduction  
Excellent viscosity/temperature properties  
Excellent ageing resistance  
All sealing materials compatibility

## Application

### APPLICATION

Quelle QX - Trans X Range is used in powered transmission and axle drives for cars, highway light and heavy duty trucks, busses, and vans where an API GL-5 is required.

## Specification

### Performance level:

GL5

## Typical Characteristics

		GL5	GL5	GL5	GL5	GL5	GL5
Property	Unit	90	140	75W90	75W140	85W90	85W140
Density @15 °C	Kg/l	0.89	0.89	0.86	0.872	0.9	0.91
Viscosity 100 °C	mm <sup>2</sup> /s	20	29.6	15.7	24.4	15	27.8
Viscosity 40 °C	mm <sup>2</sup> /s	229	443	115	170	144	369
Viscosity Index	-	101	95	144	175	105	100
Pour Point	°C	-18	-12	-45	-48	-30	-18
Flash Point	°C	210	230	210	207	210	210

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.  
You can download a recent material safety data sheet of this product on our website.