



SNA GmbH

Hochleistungs - Schmierstoffe



Gutenbergstraße 2d, 59174
Kamen, Germany
Tel. +49 (0) 151 64695831
Internet: <http://snalube.com>
e-mail: info@snalube.com

Product Information

Quelle QX - Ultra Plus 15W40 CI-4

Description

Quelle QX- Ultra Plus 15W40 CI4 is a high performance lubricant used in on-road diesel engine oil. It Contains excellent viscosity stability in service, guaranteeing effective engine lubrication in severe conditions. Outstanding detergent, dispersant and anti-wear properties.

It provides :

- High thermal and oxidation stability
- Advanced detergency
- Excellent low temperature properties

Application

It is recommended for Euro 3, and previous engines of most European and American manufacturers.. Recommended for use in a wide range of heavy-duty applications and operating environments

Specifications

Performance level:

ACEA E7
API CI-4
MB- 228.3
MB- 229.1
Volvo VDS-3;
Renault Truck RLD-2;
MAN M 3275;
Cummins CES 20076; Cummins CES 20077; Cummins CES 20078;

Typical Characteristics

15W40 CI4		
Property	Unit	Typical Values
Density at 15 °C	kg/l	0.875
Viscosity -15 °C	mPa.s	7000
Viscosity 40 °C	mm ² /s	120
Viscosity 100 °C	mm ² /s	15.7
Viscosity Index		140
Flash Point COC	°C	220
Pour Point	°C	-34
Total Base Number	mgKOH/g	11
Sulphate Ash	%	1.12

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.
You can download a recent material safety data sheet of this product on our website.